

Hydraulic Hose Press



Technical Specifications

- Any Coupling should be pressed for 3 / 16 - 3 inc dimensions. Safe and speedy machine fit to serial pressing.
- 8 pcs clamping device move simultaneously inside of the taper head for doing ressing. This simultaneous advance eliminates taper, astringency and possible pressing failures.
- Machine has 96 clamping devices , Clamping is done with hydraulic working principle.
- Clamping devices and head are manufactured 4140 working material applied heat treatment to extend life time. By this method crush, crack etc deformations are eliminated.
- Suitable clamping pressure is calibrated on table value for 20-350 bar range.
- Micrometer calibration option is available for Sensitive Calibrations.
- Foot switch is standart for Easy Working.
- Lower-Top swich and power cutter button available for emergency situations.
- Preferred equipments ;
Hydraulic : aron, oleostar;
Electricity : emas, simens
- All clamping dimensions machines are manufactured for special orders.
- All CE patented machines are mechanic quarenteed for 2 years.
- 480 x 1360 x 1100 (width x lenght x height) mm
- Total Weight : 700 kg
- Engine: 4 kw 1500 rpm/min
- Clamping speed average : 12 pcs / min



Main Address: Karatuz Cd. İş Turkuaz Sitesi A3 Blok 57/28 Bağlıca/Etimesgut/Ankara
Office Address: Serhat Mh. 1354 Sk. No:6 Yenimahalle / Ankara
Phone: 03122343371 Cell: 05306281321